

Technical Data Sheet



JOTUN Premium mur filler

Type

A texture filling and crack filling primer and intermediate coating for outdoor use.

Features and benefits

Extends the maintenance interval. Bridges small cracks and fills irregularities. Permeable with regard to water vapor and CO₂.

Breathable. Water repellent. Prevents flaking.

Recommended use

The product is recommended for outdoor use only.

For use in the JOTUN Premium mur system. Recommended for use on all plastered surfaces. Especially suitable for old plaster facades with cracks, flaking or other irregularities. Shall be painted with JOTUN Premium mur Topcoat.

Product data

Packaging size	10 L (BASE 9 L)
Tinting	Must be tinted using Jotun Multicolor. Can be tinted with half amount of tinter.
Colours	White, can be tinted using JOTUN Multicolor with half amount of tinter. Colours will vary and are intended only as toning to give better cover for the topcoat.
Gloss level	Matt
Generic type	Undercoat, lightly structured. Contains silicone emulsion.
Solids	50 ± 2 volume%
Specific gravity	1,7
VOC for Ready-for-Use Mixture	EU limit value for this product (cat. A/c): 40 g/l. This product contains max 40 g/l VOC.

Application data

Remarks

Stir well before use. Contents of tins with different production numbers should be mixed. The product is ready for use.

Application methods

Brush and roller. The product should be applied with a brush, but can be applied with a roller and then worked into the surface using a brush. Repeated small area application. For the best possible texture and crack filling, the product should be cross brushed.

Conditions during application

The air and surface temperature must be above +5 °C and below +25 °C.

Technical Data Sheet

JOTUN Premium mur filler



Jotun Protects Property

Spreading rate per coat

Recommended 3 m²/l - 4 m²/l

Recommended film thickness per coat

Wet (calculated)

Recommended 250 µm - 333 µm

Dry (calculated)

Recommended 125 µm - 167 µm

Dilution

Do not mix in oil additives.

Cleaning of painting tools

Water and a suitable cleaning agent.

Drying times

The drying time depends on the surface temperature (min. +5 °C), absorption, humidity and air circulation.

Relative Humidity (RH) 50 %

Air temperature 10 °C 23 °C

Substrate temperature 10 °C 23 °C

Dust dry 6-8 h 3-4 h

Dry to over coat, minimum 24 h 12 h

Directions for use

Surface preparation

The substrate must be clean, sound and dry: New plaster should be applied according to NS 3420. Loose paint and plaster, and possible lime wash must be removed. Fungus, soot and other contamination must be removed, using a suitable cleaning agent (detergent) - window panels should be covered. New plaster should be allowed to cure for minimum 4 weeks before treatment. Any constructional weaknesses must be repaired before painting.

Primer

Untreated brick / plaster must be primed with JOTUN Premium mur Primer.

Undercoat

JOTUN Premium mur filler. Apply with brush - cross brushing/random direction. Shall be painted with JOTUN Premium mur Topcoat.

Maintenance

Storage

Frost free freight and storage. In storage and in transport keep the container upright.

Disposal of waste

Liquid paint must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



Technical Data Sheet

JOTUN Premium mur filler



Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Miscellaneous

QR-code

How to (1) / Technical (2)

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.