

Technical Data Sheet



Jotun Premium mur Primer

Product description

Type

Unpigmented, water soluble primer based on silicone emulsion, for outdoor use.

Features and benefits

Good adhesion. Compensates absorption differences in the substrate. The product has good penetration and adhesion, is permeable and water repellent.

Recommended use

The product is recommended for outdoor use only.

To be used as primer on previously untreated masonry, as well as masonry that has become absorbant or chalked after cleaning. The product is used as a primer under JOTUN Premium mur system.

Product data

Packaging size	10 L
Colours	Colourless.
Generic type	Unpigmented primer based on silicone emulsion.
Solids	10 ± 2 volume%
Specific gravity	1
VOC for Ready-for-Use Mixture	EU limit value for this product (cat. A/g): 30 g/l. This product contains max 30 g/l VOC.

Application data

Remarks

Stir well before use. The product should not form a film. Paint should be regarded as a semi-manufacture. The result is dependent on construction, the condition of the substrate, temperature, application etc.

Application methods

Brush, roller or spray. Brush is recommended. Apply from below and upwards.

Conditions during application

Temperature of air and substrate must be above +5 °C and below +25 °C during painting.

Spreading rate per coat

Dependant on the surface texture.

Technical Data Sheet

Jotun Premium mur Primer



Jotun Protects Property

Cleaning of painting tools

Water and a suitable cleaning agent.

Drying times

The drying time depends on the surface temperature (min. +5 °C), absorption, humidity and air circulation.

Relative Humidity (RH) 50 %

Air temperature	10 °C	23 °C
Substrate temperature	10 °C	23 °C
Dust dry	2-4 h	1-2 h
Dry to over coat, minimum	10 h	5 h

Directions for use

Surface preparation

The substrate must be clean, sound and dry: New plaster should be applied according to NS 3420. Loose paint and plaster, and possible lime wash must be removed. Fungus, soot and other contamination must be removed, using a suitable cleaning agent (detergent) - window panels should be covered. Apply a suitable anti fungal treatment in accordance with the user instructions. New plaster should be allowed to cure for minimum 4 weeks before treatment. Any constructional weaknesses must be repaired before painting.

Primer

Jotun Premium mur Primer. Apply from below and upwards to untreated and bare masonry/plaster. The product should not form a film. Use JOTUN Premium mur's recommended system.

Storage

In storage and in transport keep the container frost free and upright.

Disposal of waste

Liquid paint must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Technical Data Sheet

Jotun Premium mur Primer



Jotun Protects Property

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.